



### Multipair Individually and Overall Screened Cables-Belden

#### Equivalent 8178

##### » Application


These cables have individually screened pairs laid up in a Foil & Braid screen. Each individually screened pair has a 24AWG stranded tinned copper drain wire. These cables are suitable for EIA RS-232 and EIA RS-422 applications, used as computer cables.

##### » Construction

- » Conductor: Tinned copper wire.
- » Insulation: Foam PE.
- » Individual Screen: Aluminium/

Polyester tape.

- » Drain Wire: Tinned copper wire.
- » Overall Screen1: Aluminium/Polyester tape.
- » Overall Screen2: Tinned copper braid, 65% coverage.
- » Sheath: PVC (V type)/LSZH (H type).
- » Insulation Colour: Black & Red, Black & White, Black & Green, Black & Blue, Black & Yellow, Black & Brown, Black & Orange, Red & White, Red & Green, Red & Blue, Red & Yellow, Red & Brown, Red & Orange, Green & White, Green & Blue, Green & Yellow, Green & Brown, Green & Orange.



##### » Electrical & Mechanical Characteristics

AWG		24
Conductor Construction		7x0.2
UL Style		2493
Maximum Conductor Resistance	Ω/km	85
Voltage Rating	V	300
Nominal Capacitance Conductor to Conductor	pF/m	41
Nominal Capacitance Conductor to Screen	pF/m	72
Bending Radius		10xOverall Diameter
Operating Temperature	°C	-40~60

##### » Dimensions

Ordering Code	No. of Pairs	Insulation Thickness	Sheath Thickness	Overall Diameter
		mm	mm	mm
BE118178V	18	0.47	1.22	17.4
BE118178H	18	0.47	1.22	17.4