



Multipair Individually Screened Cables-Belden Equivalent 9731

» Application

These cables have individually screened pairs laid up. Each individually screened pair has a 24AWG stranded tinned copper drain wire. These cables are suitable for RS-422 applications, used as computer cables.


» Construction

- » Conductor: Tinned copper wire.
- » Insulation: Foam PE.
- » Individual Screen: Aluminium/

Polyester tape.

- » Drain Wire: Tinned copper wire.
- » Sheath: PVC (V type)/LSZH (H type).

» Insulation Colour: Black & Red, Black & White, Black & Green, Black & Blue, Black & Yellow, Black & Brown.



» Electrical & Mechanical Characteristics

AWG		24
Conductor Construction		7x0.2
UL Style		2493
Maximum Conductor Resistance	Ω/km	85
Voltage Rating	V	300
Nominal Capacitance Conductor to Conductor	pF/m	41
Nominal Capacitance Conductor to Screen	pF/m	76
Bending Radius		10xOverall Diameter
Operating Temperature	°C	-20~60

» Dimensions

Ordering Code	No. of Pairs	Insulation Thickness	Sheath Thickness	Overall Diameter
		mm	mm	mm
BE119731V	6	0.47	1.22	10.7
BE119731H	6	0.47	1.22	10.7