




# NF F 63-826 Rolling Stock Cables

## NF F 63-826 Standard Wall Unsheathed Single Core 500V, 1000V, 1500V, 3000V



A. Conductor B. Insulation

### Application

These cables are used as power and control cable for protected installations inside and outside of rail and transport vehicles, where handling and installation cost are an important factor, suitable for used in control, auxiliary and main circuit wiring such as cable harnesses, switchboards and control panels, driver desks etc.


### Construction

#### Conductor

Stranded tinned copper wires to IEC 60228 Class 5

#### Insulation

Special halogen free compound



### Electrical & Mechanical Properties

Nominal Voltage 500V, 1000V, 1500V, 3000V

Maximum Conductor Temperature +90/+105°C

Temperature Range -25°C ~90°C

Bending Radius 4×OD



### Standards

NF F 63-826

NF F 16-101

BS 6853

### Fire Performance in general

EN 50265-2-1; IEC 60332-1; BS 4066-1

EN 50266-2-4 + EN 50305; IEC 60332-3C;

VDE 0472 Teil 804; BS 4066-3; NFC 32070

EN 50268-2; IEC 61034-2; VDE 0472 Teil 816

EN 50267-2-1; IEC 60754-1; VDE 0472 Teil 815

EN 50267-2-2/3; IEC 60754-2; VDE 0472 Teil 813

EN 50305; NFX 70-100; NFF 63808; TM1-04; BS6853

NFF 16101; NFF 63808; BS6853

Vertical flame propagation for a single insulated wire or cable  
Fire propagation of bunched wires and cables;

Smoke density

Halogen Free

Corrosivity of gases (Acidity & Conductivity)

Toxicity index

Smoke index

### 500V

Nominal Cross Sectional Area	Number & Nominal Diameter of Strands	Nominal Insulation Thickness	Overall Diameter		Weight
			Min.	Max.	
mm <sup>2</sup>	No/mm	mm	mm	mm	kg/km
1.0	32/0.20	1.3	3.8	4.5	26
1.5	30/0.25	1.3	4.1	4.8	33
2.5	50/0.25	1.3	4.5	5.2	43
4.0	56/0.30	1.3	5.0	5.8	59
6.0	84/0.30	1.4	5.7	6.5	82
10.0	80/0.40	1.5	6.9	8.1	135
16.0	126/0.40	1.5	8.2	9.2	210



# NF F 63-826 Rolling Stock Cables

**1000V**

Nominal Cross Sectional Area	Number & Nominal Diameter of Strands	Nominal Insulation Thickness	Overall Diameter		Weight
			Min.	Max.	
mm <sup>2</sup>	No/mm	mm	mm	mm	kg/km
1.5	30/0.25	1.5	4.4	5.2	42
2.5	50/0.25	1.5	4.8	5.6	55
4.0	56/0.30	1.5	5.4	6.2	72
6.0	84/0.30	1.6	6.1	6.9	96
10.0	80/0.40	1.6	7.0	8.3	154
16.0	126/0.40	1.6	8.3	9.4	218
25.0	196/0.40	1.7	9.8	11.0	316
35.0	276/0.40	1.8	11.2	12.5	440
50.0	396/0.40	1.9	13.0	14.3	580
70.0	360/0.50	2.0	14.7	16.3	830
95.0	475/0.50	2.0	16.6	18.4	1040
120.0	608/0.50	2.1	18.6	20.5	1310

**1500V**

Nominal Cross Sectional Area	Number & Nominal Diameter of Strands	Nominal Insulation Thickness	Overall Diameter		Weight
			Min.	Max.	
mm <sup>2</sup>	No/mm	mm	mm	mm	kg/km
1.5	30/0.25	2.3	6.0	6.8	59
2.5	50/0.25	2.3	6.4	7.2	73
4.0	56/0.30	2.3	7.0	7.8	91
6.0	84/0.30	2.3	7.5	8.3	120
10.0	80/0.40	2.3	8.4	9.7	160
16.0	126/0.40	2.3	9.7	10.8	235
25.0	196/0.40	2.3	11.0	12.2	330
35.0	276/0.40	2.4	12.4	13.7	480
50.0	396/0.40	2.5	14.2	15.5	610
70.0	360/0.50	2.7	16.1	17.7	860
95.0	475/0.50	2.7	18.0	19.8	1070
120.0	608/0.50	2.8	20.0	21.9	1340
150.0	756/0.50	2.8	21.8	23.8	1620
185.0	925/0.50	2.9	23.7	25.9	1940
240.0	1221/0.50	3.1	26.6	29.1	2550
300.0	1525/0.50	3.45	29.4	31.9	2950

**3000V**

Nominal Cross Sectional Area	Number & Nominal Diameter of Strands	Nominal Insulation Thickness	Overall Diameter		Weight
			Min.	Max.	
mm <sup>2</sup>	No/mm	mm	mm	mm	kg/km
2.5	50/0.25	3.1	8.0	8.8	94
4.0	56/0.30	3.1	8.5	9.5	124
6.0	84/0.30	3.1	8.8	9.9	135
10.0	80/0.40	3.1	10.0	11.3	200
16.0	126/0.40	3.1	11.2	12.4	265
25.0	196/0.40	3.1	12.5	13.8	375
35.0	276/0.40	3.2	13.9	15.3	493
50.0	396/0.40	3.3	15.7	17.2	680
70.0	360/0.50	3.4	17.5	19.1	930
95.0	475/0.50	3.5	19.5	21.4	1066
120.0	608/0.50	3.6	21.6	23.5	1530
150.0	756/0.50	3.6	23.3	25.5	1740
185.0	925/0.50	3.7	25.2	27.6	2100
240.0	1221/0.50	3.9	28.1	31.7	2460
300.0	1525/0.50	4.45	31.4	35.0	3050