



Caledonian



Cables For Oil Industry

www.caledonian-cables.com

marketing@caledonian-cables.com

600V/1000V XLPE Insulated Overall Screened & Aluminum Wire Armored Cable to IEC 60502-1

XLPE Insulated Overall Screened & Aluminum Wire Armored Cable 1C35



APPLICATIONS

These cables are used for electricity supply in low voltage installation system. They are suitable for installation in indoors and outdoors, in cable ducts, under ground, in power and switching stations, local energy distributions, industrial plants and where aliphatic and aromatic hydrocarbon may be present or where require chemical and mechanical protections.

CABLE CONSTRUCTION

Conductor: Stranded copper

Insulation: XLPE

Inner sheath: PVC. Color: black

Screen: aluminum/polyethylene tape with tinned copper drain wire

Inner sheath: HDPE. Color: black

Intermediate sheath: Polyamide

Aarmor: Aluminum wire

Sheath: Special PVC. Color: black

COLOUR CODE

1 Core: Red or Black

PHYSICAL AND THERMAL PROPERTIES

Rated voltage: 600V/1000V

Fire retardance: IEC 60332-3-22

Operating temperature: -20~60°C

Max. conductor operating temperature: 90°C

Chemical resistance: Aliphatic and aromatic hydrocarbon resistance

DIMENSION AND PARAMETERS

No. of Cores	Nominal Cross-sectional Area	Conductor Class	Nominal Diameter over Insulation	Diameter Over Intermediate Sheath	Overall Diameter (min.)	Overall Diameter (max.)	Nominal Diameter Over Armour	Approx. Weight



Caledonian

Cables For Oil Industry

www.caledonian-cables.com

marketing@caledonian-cables.com

	mm ²		mm	mm	mm	mm	mm	kg/km
1	35	Stranded, Class 2	8.9	12.5	19.3	21.3	16.3	732