


Caledonian Cables For Oil Industry www.caledonian-cables.com

marketing@caledonian-cables.com

600V/1000V XLPE Insulated Overall Screened & Steel Wire Armored Cable to IEC 60502-1

XLPE Insulated Overall Screened & Steel Wire Armored Cable 4C70





APPLICATIONS

These cables are used for electricity supply in low voltage installation system. They are suitable for installation in indoors and outdoors, in cable ducts, under ground, in power and switching stations, local energy distributions, industrial plants and where aliphatic and aromatic hydrocarbon may be present or where require chemical and mechanical protections.

CABLE CONSTRUCTION

Conductor: Stranded copper Insulation: XLPE Inner sheath: PVC. Color: black Screen: aluminum/polyethylene tape with tinned copper drain wire Inner sheath: HDPE. Color: black Intermediate sheath: Polyamide Armor: Galvanized steel wires Sheath: Speical PVC. Color: black

COLOUR CODE

4 Cores: Red, Yellow, Blue, Black

PHYSICAL AND THERMAL PROPERTIES

Rated voltage: 600V/1000V Fire retardance: IEC 60332-3-22 Operating temperature: -20~60°C Max. conductor operating temperature: 90°C Chemical resistance: Aliphatic and aromatic hydrocarbon resistance

DIMENSION AND PARAMETERS

No. of	Nominal	Conductor	Nominal	Diameter	Diameter	Overall	Overall	Nominal	Approx.
Cores	Cross-	Class	Diameter	Over	Over	Diameter	Diameter	Diameter	Weight
	sectional		over	ntermediate	Inner	(min.)	(max.)	Over	
	Area		Insulation	Sheath	Sheath			Armour	



Caledonian

Cables For Oil Industry

www.caledonian-cables.com

marketing@caledonian-cables.com

	mm²		mm	mm	mm	mm	mm	mm	kg/km
4	70	Stranded, Class 2	12	34.9	27	42.2	46.6	38.9	5123