


Caledonian


Cables For Oil Industry www.caledonian-cables.com

marketing@caledonian-cables.com

600V/1000V XLPE Insulated Steel Wire Armored Cable to IEC 60502-1 with Lead Cover

XLPE Insulated Steel Wire Armored Cable with Lead Cover 5C300





APPLICATIONS

These cables are used for electricity supply in low voltage installation system. They are suitable for installation in indoors and outdoors, in cable ducts, under ground, in power and switching stations, local energy distributions, industrial plants, where require hydrocarbon and mechanical protections. The lead sheath brings an enhanced resistance to aliphatic and aromatic hydrocarbon.

CABLE CONSTRUCTION

Conductor: Stranded copper

Insulation: XLPE Inner sheath: PVC

Lead cover

Intermediate sheath: PVC Armor: Galvanized steel wires Sheath: Special PVC. Color: black

COLOUR CODE

5 Cores: Red, Yellow, Blue, Black, Green

PHYSICAL AND THERMAL PROPERTIES

Rated voltage: 600V/1000V Fire retardance: IEC 60332-3-22 Operating temperature: -20~60°C

Max. conductor operating temperature: 90°C

Chemical resistance: Aliphatic and aromatic hydrocarbon resistance

DIMENSION AND PARAMETERS

No. of Cores	Nominal Cross- sectional Area	Diameter over I		Over Inner				Nominal Diameter Over Armour	
	mm²	mm	mm	mm	mm	mm	mm	mm	kg/km



Caledonian

Cables For Oil Industry www.caledonian-cables.com

marketing@caledonian-cables.com

	ſ	5	300		24.2	78.5	69.3	74.5	89.63	98.9	84.8	29895
--	---	---	-----	--	------	------	------	------	-------	------	------	-------