





# Caledonian

Cables For Oil Industry  
www.caledonian-cables.com

marketing@caledonian-cables.com

## 600V/1000V XLPE Insulated Steel Wire Armored Cable to IEC 60502-1

XLPE Insulated Steel Wire Armored Cable 2C35



### APPLICATIONS

These cables are used for electricity supply in low voltage installation system. They are suitable for installation in indoors and outdoors, in cable ducts, under ground, in power and switching stations, local energy distributions, industrial plants, where require chemical and mechanical protections.

### CABLE CONSTRUCTION

- Conductor: Stranded copper
- Insulation: XLPE
- Inner sheath: PVC. Color: black
- Aarmor: Galvanized steel wires
- Sheath: Special PVC. Color: black

### COLOUR CODE

2 Cores: Red, Black

### PHYSICAL AND THERMAL PROPERTIES

- Rated voltage: 600V/1000V
- Fire retardance: IEC 60332-3-22
- Operating temperature: -20~60°C
- Max. conductor operating temperature: 90°C
- Chemical resistance: Aliphatic and aromatic hydrocarbon resistance

### DIMENSION AND PARAMETERS

| No. of Cores | Nominal Cross-sectional Area | Conductor Class   | Nominal Diameter over Insulation | Diameter Over Inner Sheath | Overall Diameter (min.) | Overall Diameter (max.) | Nominal Diameter Over Armour | Approx. Weight |
|--------------|------------------------------|-------------------|----------------------------------|----------------------------|-------------------------|-------------------------|------------------------------|----------------|
|              | mm <sup>2</sup>              |                   | mm                               | mm                         | mm                      | mm                      | mm                           | kg/km          |
| 2            | 35                           | Stranded, Class 2 | 8.9                              | 20.1                       | 26.09                   | 28.8                    | 23.3                         | 1899           |