





## Caledonian

Cables For Oil Industry  
www.caledonian-cables.com

marketing@caledonian-cables.com

### Screened TFN Cable

11C16AWG, 600V, Rated 90°C



### APPLICATIONS

These cables are used in class 1, Division 2 Hazardous locations, may be installed in trays, wire ways, ducts, conduit and aerially when properly supported by a messenger. They are approved for direct burial, wet or dry locations and outdoors in cable trays where a sunlight resistant rating is required.

### STANDARDS

ICEA S-73-532; UL 1277; UL 66

### CABLE CONSTRUCTION

Conductor: Bare, annealed copper conforming to ASTM B3 and B8

Insulation: Flame-retardant PVC/Nylon type TFN per UL 66

Binder tape

Screen: Aluminum tape

Drain Wire: 18 AWG (7w) tinned copper

Ripcord: Nylon

Jacket: Special PVC, flame retardant, UL listed sunlight and moisture resistant, meeting the requirements of UL 1277. Color: Black

Chemical resistance: Aliphatic and aromatic hydrocarbon resistance

### COLOUR CODE

Color coded per Method #1-E2 per ICEA S-73-532

### DIMENSION AND PARAMETERS

No. of Cores	AWG Size	PVC Thickness	Nylon Thickness	Nominal Jacket Thickness	Nom. Overall Diameter	Approx. Weight	Ampacity
		mm	mm	mm	mm	kg/km	amps
11	16	0.38	0.1	1.14	12.8	257	4