

Caledonian


Cables For Oil Industry www.caledonian-cables.com

marketing@caledonian-cables.com

Unscreened Composite THHN/THWN-2 Cable

4C14AWG Control cables+3C6AWG Power cables 600V, Rated 90°C





APPLICATIONS

These cables are use in class 1, Division 2 Hazardous locations, may be installed in trays, wire ways, ducts, conduit and aerially when properly supported by a messenger. They are approved for direct burial, wet or dry locations and outdoors in cable trays where a sunlight resistant rating is required.

STANDARDS

ICEA S-73-532; ICEA S-95-658; UL 1277; UL 83

CABLE CONSTRUCTION

Conductor: Bare, annealed copper conforming to ASTM B3 and B8 4 Control Conductors with 3 Power conductors and 1 Ground Wire Insulation: Flame-retardant PVC/Nylon type THHN/THWN-2 per UL 83

Ground wire are green insulated

Binder tape Ripcord: Nylon

Jacket: Special PVC, flame retardant, UL listed sunlight and moisture resistant, meeting the requirements of UL

1277. Color: Black

Chemical resistance: Aliphatic and aromatic hydrocarbon resistance

COLOUR CODE

Core identification:

Control conductors are color coded as E2 per ICEA S-73-532

Power conductors are black with numbers

DIMENSION AND PARAMETERS

Control Cable Size	Control Cable Insulation Thickness PVC/ Nylon	Power Cable Size	Power Cable Insulation Thickness PVC/ Nylon	Ground Wire	Nominal Jacket Thickness	Nom. Overall Diameter	Approx. Weight	Ampacity (Control Cable)	Ampacity (Power Cable)
AWG	mm	AWG	mm	AWG	mm	mm	kg/km	amps	amps



Caledonian Cables For Oil Industry www.caledonian-cables.com

marketing@caledonian-cables.com

	14	0.38/0.1	6	0.76/0.1	8	1.52	19.43	759	17.5	75	
--	----	----------	---	----------	---	------	-------	-----	------	----	--