



# Caledonian


Coaxial Cables

www.caledonian-cables.com

marketing@caledonian-cables.com

## M17/RG Coaxial-Cable MIL-C-17F 75Ohm

M17/6-RG 11 (RG11A/U)



### Construction

Inner conductor	Tinned copper	7 x 0.40 mm
Dielectric	Low density PE	$\Phi 7.25 \pm 0.18$ mm
Outer conductor(shield)	Plain copper	192 x 0.18 mm
Shield coverage	/	97%
Outer sheath	PVC or LSZH	$\Phi 10.3 \pm 0.18$ mm

### Electrical Mechanical Characteristics

Impedance	75±5 Ohm
Nominal capacitance	67 pF/m
Velocity of propagation	66%
Insulation resistance	>2000 Mohm.Km
Inner conductor resistance	20.5 Ohm/Km
Outer conductor resistance	4.5 Ohm/Km
Operating temperature range	-30 °C - +70 °C
Test/Operatig Voltage(max)	8KV/5KV
Copper weight	57 Kg/Km
Cable weight (approx.)	145.2 Kg/Km
Screening effectiveness	>55 dB

### Attenuation

Frequency (MHz)	Attenuation (dB/100 m)	Attenuation (dB/100 ft)
50	4.2	1.28
100	6.2	1.89
200	9.3	2.84
400	13.8	4.21
500	15.5	4.73
600	17.1	5.21



# Caledonian

Coaxial Cables

[www.caledonian-cables.com](http://www.caledonian-cables.com)

[marketing@caledonian-cables.com](mailto:marketing@caledonian-cables.com)

860	20.1	6.13
1000	23.4	7.13

## Return Loss

30-300 MHz	>30dB
300-600 MHz	>27dB
600-900 MHz	>25dB