



## Caledonian



IEC60092 Offshore & Marine Cables

[www.caledonian-cables.com](http://www.caledonian-cables.com)

[marketing@caledonian-cables.com](mailto:marketing@caledonian-cables.com)

BI (i)/ BU(i) (MRE-M2XH PiMF) 150/250V Mica Tape + XLPE Insulated, LSOH (SHF1) Sheathed, Individual Screened Fire Resistant Instrumentation & Control Cables 30P1

MRE-M2XH PiMF-30P1



### APPLICATIONS

These cables are used on board of ships in all locations for fixed installations not subject to mechanical risk complying with IEC standards 60092-352 in safety circuit, where fire resistance is required. These cables are fire resistant, flame retardant, low smoke & halogen free, suitable for installations on passenger ships, as on other commercial vessels.

### STANDARDS

IEC 60092-350/360/376/IEC 60331-21/IEC 60332-1

IEC 60332-3-22/IEC 60754-1/2/IEC 61034

### CABLE CONSTRUCTION

Conductors: Class 2 stranded copper conductor.

Insulation: Mica tape + XLPE.

Cabling Element: Pair.

Individual Screen: Al/polyester tape.

Drain Wire: Tinned copper wire.

Outer Sheath: LSOH (SHF1). SHF2 can be offered upon request.

### COLOUR CODE

Pair: White/blue with printed pair number and core number.

### PHYSICAL AND THERMAL PROPERTIES

Bending Radius for Fixed Installations:  $6 \times OD$  ( $OD > 25\text{mm}$ );  $4 \times OD$  ( $OD \leq 25\text{mm}$ )

Temperature Range:  $-30^{\circ}\text{C} \sim +80^{\circ}\text{C}$

### DIMENSION AND PARAMETERS

No. of Cores $\times$ Cross-sectional Area	Nominal Insulation Thickness	Nominal Sheath Thickness	Nom. Overall Diameter	Approx. Weight
No. $\times$ mm <sup>2</sup>	mm	mm	mm	kg/km



# Caledonian

IEC60092 Offshore & Marine Cables

[www.caledonian-cables.com](http://www.caledonian-cables.com)

[marketing@caledonian-cables.com](mailto:marketing@caledonian-cables.com)

30x2x1	0.5	2	35.4	1840
--------	-----	---	------	------