





Caledonian

JIS Code Power & Control Cables

www.caledonian-cables.com

marketing@caledonian-cables.com

VVR-GRD 4C35+1G10



APPLICATIONS

For exposed wiring in air or use raceway, dry location.

STANDARDS

TIS 11-2531

CABLE CONSTRUCTION

Conductor: Stranded annealed copper

Insulation: Polyvinyl chloride (PVC)

Color: Light gray, Black, Red, Blue Ground core: Green/Yellow

Sheath: Polyvinyl chloride (PVC), white color

PHYSICAL AND THERMAL PROPERTIES

Maximum conductor temperature 70°C

Circuit voltage not exceeding 750 volts

Test voltage 2500 volts

DIMENSION AND PARAMETERS

No. of Cores	Conductor Size	No. and Dia. of Wires	Nominal Earth Conductor Area	Earth Conductor Strand Size	Nominal Insulation Thickness	Nominal Sheath Thickness	Overall Diameter (max.)	Approx. Weight	Min. Insulation Resistance at 70 °C	Current rating in the air
	mm ²	no./mm	mm ²	no./mm	mm	mm	mm	kg/km	Ohm/km	A
4+1	35	19/1.53	10	7/1.35	1.2	1.8	33.5	2070	0.0043	102