





## Caledonian

BS 6883&BS 7917 Caledonian Offshore & Marine Cables MV Flame Retardant Power & Control Cables

[www.caledonian-cables.com](http://www.caledonian-cables.com)

[marketing@caledonian-cables.com](mailto:marketing@caledonian-cables.com)

### 6.35/11kV HF-EPR Insulated, SW2/SW4 Sheathed Unarmoured Flame Retardant Power & Control Cables (Radial Field) 1C185.0



### APPLICATIONS

These medium voltage elastomeric insulated cables are designed for fixed wiring in ships and on mobile offshore units, suitable for use in power and control applications.

### STANDARDS

BS 6883

IEC 60332-3A Flame retardant

IEC 60754-1; IEC 60754-2 Corrosivity

IEC 61034-2 Smoke density

Cold bend and impact (-40°C) (on request)

CSA C22.2 No. 38-95 (on request)

### VOLTAGE RATING

6.35/11kV

### CABLE CONSTRUCTION

Conductor: Tinned copper wire stranded circular cl. 2 BS 6360/IEC 60228.

Conductor Screen: Semiconducting layer or tape.

Insulation: HF-EPR GP5 according to BS 7655 1.2.

Insulation Screen: Semiconducting layer or tape + Tinned copper tape.

Outer Sheath: Halogen free thermosetting compound SW4 according to BS 7655 2.6 or reduced halogen thermosetting compound SW2 according to BS 7655 2.6.

### COLOUR CODE

Single core : Natural colour of the compound

### MECHANICAL PROPERTIES

Minimum Internal Bending Radius: 15×OD (single core)

Temperature Range: -40°C ~ +90°C

### DIMENSION AND PARAMETERS



## Caledonian

BS 6883&BS 7917 Caledonian Offshore & Marine Cables MV Flame  
Retardant Power & Control Cables

[www.caledonian-cables.com](http://www.caledonian-cables.com)

[marketing@caledonian-cables.com](mailto:marketing@caledonian-cables.com)

| No. of Cores<br>× Cross-<br>sectional Area | Nominal<br>Insulation<br>Thickness | Nominal<br>Outer Sheath<br>Thickness | Overall<br>Diameter (min.) | Overall<br>Diameter (max.) | Approx. Weight |
|--|------------------------------------|--------------------------------------|----------------------------|----------------------------|----------------|
| No.×mm <sup>2</sup>                        | mm                                 | mm                                   | mm                         | mm                         | kg/km          |
| 1x185                                      | 3.4                                | 1.8                                  | 29.8                       | 32.9                       | 2769           |