




# Caledonian

Military Cables

www.caledonian-cables.com

marketing@caledonian-cables.com

## MS 25471 (Mil-W-8777 Wire) 1C1AWG



### APPLICATIONS

These silicone rubber primary insulated single-core MS 25471 (Mil-W-8777 Wire) cables are used in aircraft and missiles using any combination of electrical loading and ambient temperature. It has low moisture absorption and generally good resistance to chemicals.

### VOLTAGE RATING

600V

### CABLE CONSTRUCTION

Conductor: Stranded, silver-coated copper conductor

Insulation: Silicone rubber primary insulation

Braid: Inner braid glass fibers or combination of glass fibers and polyester fibers impregnated with high temperature finisher

Jacket: Outer jacket of polyester fiber impregnated with high temperature finisher

### COLOUR CODE

Black or White per MIL-STD-104; Tan (per MIL-W-8777 spec)

### PHYSICAL AND THERMAL PROPERTIES

Temperature Range: 200°C

### DIMENSION AND PARAMETERS

AWG Size	Conductor Stranding	Overall Diameter (min.)	Overall Diameter (min.)	Overall Diameter (max.)	Overall Diameter (max.)	Approx. Weight	Max. Resistance at 20°C
		in	mm	in	mm		LBS/MFT
1	817/30	0.45	11.43	0.47	11.938	317	0.15