


## marketing@caledonian-cables.com

# STJ(SEX) Cables - PTFE(FEP) Tape Jacket Over Shield 1C16AWG



### **APPLICATIONS**

These PTFE insulated MIL-W-16878D shielded PTFE cables are used in electronic equipment. This cables are resistant to acids, alkalis, oil, flame, moisture, solvents and fungus.

### **VOLTAGE RATING**

600V

## **CABLE CONSTRUCTION**

Conductor: stranded silver plated copper(also available nickel plated copper)

Insulation: Type E extruded PTFE Insulation Wall Thickness: 0.006"

Shield: Braided silver plated copper shield (85% Coverage)

Jacket: Tape wrapped PTFE (STJ) or Extruded FEP (SXE) Jacket (White preferred)

## **COLOUR CODE**

Standard Color Code: 1: White; 2: Black; 3: Red; 4: Green; 5:Yellow; 6:Blue

## PHYSICAL AND THERMAL PROPERTIES

Temperature Range: -65°C to +200°C

(Nickel-plated conductors PTFE jacket: 260°C) (Nickel-plated conductors FEP jacket: 200°C)

### **DIMENSION AND PARAMETERS**

No. of Conductor	AWG Size	Conductor Stranding	Shield Diameter	Shield Diameter	Approx. Overall Diameter	Approx. Overall Diameter	Approx. Weight
			in	mm	in	mm	LBS/MFT
1	16	19/29	0.1	2.54	0.117	2.972	17