



# Caledonian


Mining Cables (VDE Standard)

[www.caledonian-cables.com](http://www.caledonian-cables.com)

[marketing@caledonian-cables.com](mailto:marketing@caledonian-cables.com)

## Cables for Underground Mining

H07RN-F/A07RN-F 450/750V Harmonized Rubber Cables 4G185



## APPLICATIONS

These cables are designed for the connection of heating units, industrial tools, mobile equipment and machines, e.g. vulcanisation plates, hand-operated equipment, transportable motors etc., under normal mechanical loads in dry and damp areas, outdoors and in explosion hazard areas, as well as in industrial and agricultural applications and on building sites.

## STANDARDS

DIN VDE 0282 Part1 and Part 4

HD 22.1/HD 22.4

## VOLTAGE RATING

450/750V

## CABLE CONSTRUCTION

Conductors: Stranded copper conductor, class 5 according to DIN VDE 0295/HD 383 S2.

Insulation: Rubber type EI4 according to DIN VDE 0282 Part 1/HD 22.1.

Inner Sheath: NR/SBR rubber type EM1.

Outer Sheath: CR/PCP rubber type EM2.

## DIMENSION AND PARAMETERS

No. of Cores × Cross- sectional Area	Nominal Insulation Thickness	Nominal Inner Sheath Thickness	Nominal Outer Sheath Thickness	Overall Diameter (min.)	Overall Diameter (max.)	Approx. Weight
No. × mm <sup>2</sup>	mm	mm	mm	mm	mm	kg/km
4G185	2.2	2.8	4.2	64	71	9850