



# Caledonian


Mining Cables (VDE Standard)

www.caledonian-cables.com

marketing@caledonian-cables.com

## Cables for Underground Mining

N3GHSSYCY Medium Voltage Cable 3×25+3×16/3E+3×2.5ST+UEL



## APPLICATIONS

These cables are used for the connection of mobile operating equipment, in mines and underground excavations with hazardous environments, in stationary operation, e.g. high-voltage transformers in mining and tunnelling.

## STANDARDS

VDE 0250 Part 605

## VOLTAGE RATING

8.7/15kV

## CABLE CONSTRUCTION

**Conductors:** Flexible stranded copper conductor, class 5 according to DIN VDE 0295.

**Insulation:** EPR compound type 3GI3.

**Electrical Field Control:** Inner and outer semiconductive layer of semiconductive rubber.

**Pilot Cores:** Stranded copper conductor with EPR insulation.

**Earth Conductor:** Spiral of copper wires over the outer semi-conductive layer of the cores.

**Inner Sheath:** PVC compound type YM5.

**Monitoring Conductor:** Conductive tape serving and overall concentric Cu wire spinning.

**Intermediate Sheath:** PVC compound type YM5.

**Armour:** Braid of galvanized steel wires.

**Outer Sheath:** PVC compound type YM5.

## DIMENSION AND PARAMETERS

No. of Cores × Cross-sectional Area	Overall Diameter (min.)	Overall Diameter (max.)	Approx. Weight
No.×mm <sup>2</sup>	mm	mm	kg/km



# Caledonian

Mining Cables (VDE Standard)

[www.caledonian-cables.com](http://www.caledonian-cables.com)

[marketing@caledonian-cables.com](mailto:marketing@caledonian-cables.com)

3×25+3×16/3E +3×2.5ST+UEL	58	62	6810
------------------------------	----	----	------