


Caledonian

Mining Cables (VDE Standard) www.caledonian-cables.com marketing@caledonian-cables.com

Cables for Underground Mining

NSSHOEU-J 0.6/1kV Heavy Duty Flexible Cable 3C70/35





5GM5 Rubber Outer Sheath GM1b/5GM3 Rubber Inner Sheath Stranded Tinned Copper Conductor 3GI3 Insulation

APPLICATIONS

These cables are designed for the connection of mobile equipment and machines under very high mechanical loads in dry and damp areas, outdoors and in explosion hazard areas, particularly in mining and industry, quarries and building sites.

STANDARDS

VDE 0250 Part 812

CABLE CONSTRUCTION

Conductors: Flexible stranded tinned copper conductor, class 5 according to DIN VDE 0295.

Insulation: Heat resistant EPR type 3GI3.

Inner Sheath: SR/SBR/PCP/CR type GM1b/5GM3.

Outer Sheath: Chlorinated rubber PCP/CR type 5GM5, abrasion and tear resistant, oil resistant and flame retardant.

DIMENSION AND PARAMETERS

No. of Cores × Cross-sectional Area	Overall Diameter (min.)	Overall Diameter (max.)	Approx. Weight
No.×mm ²	mm	mm	kg/km
3×70/35	46	51	4450