

Caledonian


Mining Cables (ICEA & CSA Standard)

www.caledonian-cables.com marketing@caledonian-cables.com

Portable Power Cables

Type G Three-Conductor Round Portable Power Cable 2kV 3C6AWG





APPLICATIONS

These cables are designed for use with mobile mining equipment, such as continuous miners, cutting or loading machines, conveyors, drills or pumps.

STANDARDS

ICEA S-75-381/NEMA WC 58 ASTM B 172/ASTM B 33 CAN/CSA C22.2 No. 96

CABLE CONSTRUCTION

Conductors: Stranded annealed tinned copper conductor.

Insulation: Ethylene Propylene Rubber (EPR).

Grounding Conductor: Tinned copper conductor with an optional green outer covering.

Jacket:Reinforced heavy-duty/extra-heavy-duty Chlorinated Polyethylene (CPE), black. (Cables having a nominal outside diameter of more than 2.0 inches require extra-heavy-duty jackets.)

Options:

Other jacket materials such as CSP/PCP/NBR/PVC are available upon request.

Two-layer jacket with reinforcing fibre between the two layers can be offered as an option.

COLOUR CODE

Conductor Identification According to ICEA S-75-381:

3 Cores:Black+White+Red

PHYSICAL AND THERMAL PROPERTIES

Minimum Bending Radius: 6×OD

Maximum Conductor Operating Temperature: +90°C

DIMENSION AND PARAMETERS

No. of	AWG	No. of	Nominal	Nominal	Ground	Nominal	Nominal	Approx.	Approx.	Approx.	Ampacity
Cores	Size	Strands	Insulation	Insulation	Wire	Jacket	Jacket	Overall	Overall	Weight	
			ThicknessThickness ThicknessThicknessDiameter Diameter								



Caledonian

Mining Cables (ICEA & CSA Standard)

www.caledonian-cables.com marketing@caledonian-cables.com

			in	mm	AWG	in	mm	in	mm	kg/km	amps
3	6	168	0.06	1.5	10	0.14	3.6	1.01	25.7	1131	79