

## Caledonian


### Mining Cables (ICEA & CSA Standard)

www.caledonian-cables.com marketing@caledonian-cables.com

#### Portable Power Cables

Type W Two-Conductor Round Portable Power Cable 2kV 2C3/0AWG





#### **APPLICATIONS**

These cables are designed for general use where bare grounding conductors are not required or desired.

#### **STANDARDS**

ICEA S-75-381/NEMA WC 58 ASTM B 172/ASTM B 33 CAN/CSA C22.2 No. 96

#### CABLE CONSTRUCTION

Conductors: Stranded annealed tinned copper conductor.

Insulation: Ethylene Propylene Rubber (EPR).

Jacket:Reinforced heavy-duty/extra-heavy-duty Chlorinated Polyethylene (CPE), black. (Cables having a nominal outside diameter of more than 2.0 inches require extra-heavy-duty jackets.)

#### Options:

Other jacket materials such as CSP/PCP/NBR/PVC are available upon request.

Two-layer jacket with reinforcing fibre between the two layers can be offered as an option.

#### **COLOUR CODE**

Conductor Identification According to ICEA S-75-381:

2 Cores:Black+White

#### PHYSICAL AND THERMAL PROPERTIES

Minimum Bending Radius: 6×OD

Maximum Conductor Operating Temperature: +90°C

#### **DIMENSION AND PARAMETERS**

No. of Cores	AWG Size	Strands	Nominal Insulation Thickness	Insulation	Jacket	Jacket	Overall	Overall	Weight	Ampacity
			in	mm	in	mm	in	mm	kg/km	amps



# Caledonian

## Mining Cables (ICEA & CSA Standard)

www.caledonian-cables.com marketing@caledonian-cables.com

2	3/0	658	0.08	2	0.19	4.8	1.77	45	3870	286
										4