

## Caledonian


## Mining Cables (AS\_NZS Standard)

www.caledonian-cables.com marketing@caledonian-cables.com

### AS/NZS 1802:2003 Reeling & Trailing Cables

Type 245 1.1KV 3C95





#### **APPLICATIONS**

These very flexible cables are mainly used as longwall shearer cables, and also for continuous miners and peripheral longwall cables. Cable has 3 central pilots for earth continuity monitoring and for control circuits.

#### **STANDARDS**

AS/NZS 1802:2003

**AS/NZS 1125** 

**AS/NZS 3808** 

AS/NZS 5000.1

#### CABLE CONSTRUCTION

3×Conductors: Flexible stranded tinned annealed copper conductor.

Insulation: EPR.

Insulation Screen: Semiconductive elastomer.

Cradle Separator: Semiconductive PCP.

Overall Core Screen: Semiconductive PCP filling and covering.

3×Interstitial Earth Conductor: Semiconductive PCP covered flexible stranded tinned copper conductor.

3×Central Extensible Pilot: EPR covered flexible stranded tinned copper conductor.

Textile Reinforcement: Open-weave braid reinforcement.

Sheath: Heavy duty PCP sheath. Heavy duty CPE/CSP sheath can be offered upon request.

#### **COLOUR CODE**

Rotational sequence of core colours: Red, Black, White, Black, Blue, Black

#### **DIMENSION AND PARAMETERS**

Nominal	No./	Earth	Earth	Pilot	Pilot	Nominal	Nominal	Nom.	Approx.
Cross-	Nominal	Conductor	Conductor	Conductor	Conductor	Insulation	Sheath	Overall	Weight
sectional	Diameter	Strand	Thickness	Strand	Thickness	Thickness	Thickness	Diameter	
Area	of	Size	of	Size	of				
	Strands		Covering		Covering				
mm²	no./mm	no./mm	mm	no./mm	mm	mm	mm	mm	kg/km



# Caledonian

# Mining Cables (AS\_NZS Standard)

www.caledonian-cables.com marketing@caledonian-cables.com

95	1332/0.3	150/0.3	1	28/0.25	0.8	2	5.6	60.4	630
	l					l			