


Caledonian


Mining Cables (AS_NZS Standard)

www.caledonian-cables.com marketing@caledonian-cables.com

AS/NZS 2802:2000 Reeling & Trailing Cables

Type 412 Class2 1.1KV 3C16





APPLICATIONS

These cables with green/yellow earths and pliable armour for mechanical protection may be used in applications where damage is likely and armour can reduce cases of costly downtime, suitable installed as feeder cables in sand mining operations.

STANDARDS

AS/NZS 2802:2000

AS/NZS 1125

AS/NZS 3808

AS/NZS 5000.1

CABLE CONSTRUCTION

3×Conductors: Flexible stranded tinned annealed copper conductor.

Insulation: EPR.

Insulation Screen: Semiconductive elastomer.

Filler: Elastomer centre filler.

3×Interstitial Earth Conductor: EPR covered flexible stranded tinned copper conductor.

Inner Sheath: PCP sheath. CPE/CSP sheath can be offered upon request.

Pliable Armour: Galvanized low carbon (mild) steel strands.

Outer Sheath: Heavy duty PCP sheath. Heavy duty CPE/CSP sheath can be offered upon request.

COLOUR CODE

Rotational sequence of core colours: Red, Green/Yellow, White, Green/Yellow, Blue, Green/Yellow

DIMENSION AND PARAMETERS

Nominal	No./	Earth	Earth	Nominal	Nominal	Nominal	Pliable	Nom.	Approx.
Cross-	Nominal	Conductor	Conductor	Insulation	Inner	Outer	Armour	Overall	Weight
sectional	Diameter	Strand	Thickness	Thickness	Sheath	Sheath	Size	Diameter	
Area	of	Size	of		Thickness	Thickness			
	Strands		Covering						
mm²	no./mm	no./mm	mm	mm	mm	mm	no./mm	mm	kg/km



Caledonian

Mining Cables (AS_NZS Standard)

www.caledonian-cables.com marketing@caledonian-cables.com

16	126/0.4	81/0.3	0.6	1.6	2.5	3.8	7/0.9	38.3	265