

Caledonian


Mining Cables (AS_NZS Standard)

www.caledonian-cables.com marketing@caledonian-cables.com

AS/NZS 2802:2000 Reeling & Trailing Cables

Type 441 Class2 1.1KV 3C240





APPLICATIONS

These Class 2 cables are designed for many uses, suitable for trailing and also suitable for reeling applications, have one central pilot and a semiconductive cradle supporting and protecting the power cores, which makes these cables less likely to be damaged from crushing and squashing.

STANDARDS

AS/NZS 2802:2000 AS/NZS 1125

.

AS/NZS 3808

AS/NZS 5000.1

CABLE CONSTRUCTION

3×Conductors: Flexible stranded tinned annealed copper conductor.

Insulation: EPR.

Insulation Screen: Semiconductive elastomer.

Cradle Separator: Semiconductive PCP.

Overall Core Screen: Semiconductive PCP filling and covering.

3×Interstitial Earth Conductor: Semiconductive PCP covered flexible stranded tinned copper conductor.

1×Central Extensible Pilot: EPR covered flexible stranded tinned copper conductor.

Textile Reinforcement: Open-weave braid reinforcement.

Sheath: Heavy duty PCP sheath. Heavy duty CPE/CSP sheath can be offered upon request.

COLOUR CODE

Rotational sequence of core colours: Red, Black, White, Black, Blue, Black. The central pilot core is grey.

DIMENSION AND PARAMETERS

Nominal	No./	Earth	Earth	Pilot	Pilot	Nominal	Nominal	Nom.	Approx.
Cross-	Nominal	Conductor	Conductor	Conductor	Conductor	Insulation	Sheath	Overall	Weight
sectional	Diameter	Strand	Thickness	Strand	Thickness	Thickness	Thickness	Diameter	
Area	of	Size	of	Size	of				
	Strands		Covering		Covering				
mm²	no./mm	no./mm	mm	no./mm	mm	mm	mm	mm	kg/km



Caledonian

Mining Cables (AS_NZS Standard)

www.caledonian-cables.com marketing@caledonian-cables.com

240	672/0.67	119/0.67	1.2	40/0.2	0.8	2.8	8	83.3	1329