



## Caledonian

Mining Cables (AS\_NZS Standard) www.caledonian-cables.com marketing@caledonian-cables.com

#### AS/NZS 2802:2000 Reeling & Trailing Cables

Type 450 Class1 3.3KV 3C25





### **APPLICATIONS**

These cables are suitable for supply of power to a wide range of applications, from dragline cable to slow reeling applications, where copper screened cable is required but light weight and smaller dimensions are also desired.

#### STANDARDS

AS/NZS 2802:2000 AS/NZS 1125 AS/NZS 3808 AS/NZS 5000.1

#### CABLE CONSTRUCTION

3×Conductors: Flexible stranded tinned annealed copper conductor.

Conductor Screen: Semiconductive compound.

Insulation: EPR.

Insulation Screen: Semiconductive elastomer.

Composite Screen: Tinned annealed copper braiding interwove with polyester yarn, covered with semiconductive tape.

Filler: Elastomer centre filler.

2×Interstitial Earth Conductor: CSP covered flexible stranded tinned copper conductor.

1×Interstitial Pilot: EPR covered flexible stranded tinned copper conductor.

Textile Reinforcement: Open-weave braid reinforcement.

Sheath: Extra-heavy duty PCP sheath. Extra-heavy duty CPE/CSP sheath can be offered upon request.

#### COLOUR CODE

Rotational sequence of core colours: Red, Black, White, Black, Blue, Grey

#### DIMENSION AND PARAMETERS

Nominal Cross-	No./ Nominal	Core Screen	Core Screen	Pilot/ Earth	Pilot/ Earth	Nominal Insulation	Nominal Sheath	Nom. Overall	Approx. Weight
sectional	Diameter	Strand	Area of	Conductor	Conductor	Thickness			Wolght
Area	of Strands	Size	Screen	Strand Size	Thickness				



# Caledonian

Mining Cables (AS\_NZS Standard)

www.caledonian-cables.com

marketing@caledonian-cables.com

					of Covering				
mm²	no./mm	no./mm	mm²	no./mm	mm	mm	mm	mm	kg/km
25	209/0.4	118/0.3	8.3	120/0.3	1.4	2.2	4.8	46.9	338