

Caledonian


Mining Cables (AS_NZS Standard)

www.caledonian-cables.com marketing@caledonian-cables.com

AS/NZS 2802:2000 Reeling & Trailing Cables

Type 450 Class1 3.3KV 3C95





APPLICATIONS

These cables are suitable for supply of power to a wide range of applications, from dragline cable to slow reeling applications, where copper screened cable is required but light weight and smaller dimensions are also desired.

STANDARDS

AS/NZS 2802:2000

AS/NZS 1125

AS/NZS 3808

AS/NZS 5000.1

CABLE CONSTRUCTION

3×Conductors: Flexible stranded tinned annealed copper conductor.

Conductor Screen: Semiconductive compound.

Insulation: EPR.

Insulation Screen: Semiconductive elastomer.

Composite Screen: Tinned annealed copper braiding interwove with polyester yarn, covered with semiconductive

tape.

Filler: Elastomer centre filler.

2×Interstitial Earth Conductor: CSP covered flexible stranded tinned copper conductor.

1×Interstitial Pilot: EPR covered flexible stranded tinned copper conductor.

Textile Reinforcement: Open-weave braid reinforcement.

Sheath: Extra-heavy duty PCP sheath. Extra-heavy duty CPE/CSP sheath can be offered upon request.

COLOUR CODE

Rotational sequence of core colours: Red, Black, White, Black, Blue, Grey

DIMENSION AND PARAMETERS

Nominal Cross-	No./ Nominal	Core Screen	Core Screen	Pilot/ Earth	Pilot/ Earth	Nominal Insulation	Nominal Sheath	Nom. Overall	Approx. Weight
sectional	Diameter	Strand	Area of	Conductor	Conductor	Thickness	Thickness	Diameter	3 3
Area	of	Size	Screen	Strand	Thickness				
	Strands			Size					



Caledonian

Mining Cables (AS_NZS Standard)

www.caledonian-cables.com marketing@caledonian-cables.com

					of Covering				
mm²	no./mm	no./mm	mm²	no./mm	mm	mm	mm	mm	kg/km
95	259/0.67	123/0.4	15.5	70/0.67	1.6	2.4	6.3	64.3	734