




Caledonian

NEK606 Caledonian Offshore & Marine Cables Fire Resistant Medium Voltage Power Cables

www.caledonian-cables.com

marketing@caledonian-cables.com

P114 (Formerly P30) RFOU-HCF / TFOU-HCF 6/10(12) kV



APPLICATIONS

These cables are fire resistant, flame retardant, low smoke and halogen free, used for emergency control, power and lighting systems that need to be operational during a 1100°C hydrocarbon fire.

STANDARDS

IEC 60092-354

IEC 60092-360

IEC 60331-21

IEC 60332-1

IEC 60332-3-22

IEC 60754-1,2

IEC 61034-1,2

NEK 606:2016

VOLTAGE RATING

6/10(12) kV

CABLE CONSTRUCTION

Conductors: Circular tinned annealed stranded copper to IEC 60228 class 2.

Conductor Screen: Semi conducting material.

Insulation: Halogen-free EPR. XLPE can be offered as an option.

Insulation Screen: Semi conducting material and tinned copper wire braid.

Bedding: Halogen free compound.

Armour: Tinned copper wire braid.

Outer Sheath1: Halogen free thermosetting compound, SHF2, coloured red.

HC-fire protection: Extruded thermoplastic fire protection compound.

Taping: Lapped glass fibre tape.

Outer Sheath2: Flame retardant halogen-free thermoplastic compound, SHF1, coloured red.

MECHANICAL PROPERTIES

Bending Radius: 20×OD (during installation); 12×OD (fixed installed)



Caledonian

NEK606 Caledonian Offshore & Marine Cables Fire Resistant Medium Voltage Power Cables

www.caledonian-cables.com

marketing@caledonian-cables.com

Temperature Range: -20°C ~ +90°C

TECHNICAL CHARACTERISTICS

Nom. Cross-Section Area	Nom. Conductor Diameter	Maximum DC Resistance @20°C	Continuous Current Rating @45°C 1 Core	Short Circuit Current 1s
mm ²	mm	Ohm/km	A	A
240	19.6	0.0762	522	34340

DIMENSION AND PARAMETERS

No. of Cores × Cross-sectional Area	Nominal Insulation Thickness	Nominal Dia. over Bedding	Nominal Diameter Over Sheath 1	Approx. Overall Diameter	Approx. Weight
No. × mm ²	mm	mm	mm	mm	kg/km
1×240	3.4	33.0	39.0	72.0	8250