



# Caledonian


Railway Cables

www.caledonian-cables.com

marketing@caledonian-cables.com

## Trackside Signalling Aluminium Power Cables to BR880

RF880-RV-K-0.6/1KV-4G95SAL



### APPLICATIONS

BR880 solid sector shaped conductors for trackside signalling power supplies.

### STANDARDS

BR880

BS5467

BS6346

UNE 21123

BS EN 60702

### VOLTAGE RATING

600/1000V

### CABLE CONSTRUCTION

Conductors: Sector shaped solid plain aluminium to IEC 60228 class 2 or 5.

Insulation: XLPE type GP8 to BS7655 or PVC type TI 1 to BS 7655.

Core wrapping: PETP (Polyethylene Terephthalate).

Sheath: PVC type 9 to BS7655 (LSZH can be offered as an option).

### COLOUR CODE

4 core: Blue/Brown/Black/Grey

### PHYSICAL AND THERMAL PROPERTIES

Minimum Bending Radius: 10xOD

Temperature Range: -30°C to +70°C (during operation); -10°C +55°C (during installation)

### DIMENSION AND PARAMETERS

No. of Cores × Cross-sectional Area	Nominal Insulation Thickness	Nominal Sheath Thickness	Nom. Overall Diameter	Approx. Weight	Max. DC Resistance at 20°C
No.×mm <sup>2</sup>	mm	mm	mm	kg/km	Ω/km



# Caledonian

## Railway Cables

[www.caledonian-cables.com](http://www.caledonian-cables.com)

[marketing@caledonian-cables.com](mailto:marketing@caledonian-cables.com)

4 x 95	1.6	2.2	35.5	2100	0.32
--------	-----	-----	------	------	------



Fire Retardant  
NF C32-070-2.2(C1)  
IEC60332-3-24/EN50266-2-4



Flame Retardant  
NF C32-070-2.1(C2)  
IEC60332-1-2/EN50265-2-1




Low Corrosivity  
IEC60754-2/EN50267-2-2/3  
NF C32-074/NF C20-453



Low Smoke Emission  
IEC 61034-2 / EN 50268-2  
NF C32-073/NF C 20-902



Low Toxicity



Zero Halogen  
IEC 60754-1/EN 50267-2-1  
NF C20-454