



# Caledonian

# Submersible Pump Cables for Oil Industry www.caledonian-cables.com marketing@caledonian-cables.com

### 400°F/204°C EPDM/EPDM Round Electrical Submersible Pump Cable

QYEEY-204-3kV-3G2/0AWG





#### **APPLICATIONS**

These cables are designed for transmitting power to the submersible motor in the oil industry, suitable for installed down well in the oil industry.

#### **STANDARDS**

IEEE Std. 1018 API RP 11S5 API RP 11S6

#### **VOLTAGE RATING**

3kV

#### **CABLE CONSTRUCTION**

Conductor: Solid/stranded copper conductor.

Insulation: EPDM insulation.

Optional Barrier: Tape, braid, tape and braid, or extruded barrier, used for fluid protection and hoop strength.

Jacket:EPDM rubber. Armor:Galvanized steel.

## **DIMENSION AND PARAMETERS**

_	o. of ores	Conductor Size	AWG Size	Conductor Diameter	Diameter	Insulation	Insulation	Overall		Approx. Weight	Approx. Weight
						Thickness	Thickness	Diameter	Diameter		
		mm²		in	mm	in	mm	in	mm	kg/km	LBS/ MFT
	3	67.4	2/0	0.414	10.516	0.075	1.9	1.84	46.8	4014	2697