



Caledonian

Telephone Cables



www.caledonian-cables.com

marketing@caledonian-cables.com

INDOOR TELEPHONE CABLES

PVC Insulated Jumper Wires to CW 1257

TP1423-Y-4W05



APPLICATIONS

The jumper wires are used for interconnection between terminal blocks at main distribution frames (MDF), cross connection cabinets (CCP) and distribution frames or boxes.

STANDARDS

CW 1423 (PVC BT M154)

CABLE CONSTRUCTION

Conductors: Solid annealed tinned copper as per class 1 of BS 6360/IEC 60228.

Insulation: PVC (CW 1423).

COLOUR CODE

Standard colour code is per CW 1423.

PHYSICAL AND THERMAL PROPERTIES

Temperature range during operation (fixed state): -30°C – +70°C

Temperature range during installation (mobile state): -20°C – +50°C

Minimum bending radius: 7.5 x Overall Diameter

DIMENSION AND PARAMETERS

| Caledonian Cable Code | No. of Cores | Conductor Size | Conductor Diameter | Nominal Insulation Thickness | Nominal Diameter over Insulation (max.) | Overall Diameter (max.) | Approx. Weight |
|-----------------------|--------------|-----------------|--------------------|------------------------------|---|-------------------------|----------------|
| | | mm ² | mm | mm | mm | mm | kg/km |
| TP1423-Y-4W05 | 4 | 0.196 | 0.5 | 0.25 | 1.1 | 3.8 | 10 |