



Caledonian

Telephone Cables



www.caledonian-cables.com

marketing@caledonian-cables.com

OUTDOOR TELEPHONE CABLES

Solid PE Insulated & LAP Sheathed Air Core Cable to IEC 60708

TP708-2Y(L)2Y-300P04



APPLICATIONS

The cables are designed for use in access or trunk networks, from telephone exchange to subscriber area. The cables are suitable for installation in ducts, direct burial in the ground and also for aerial installation with integral suspension strand. An armoured option is offered for direct burial installations. A figure-8 self support option is offered for aerial installation.

STANDARDS

IEC 60708

CABLE CONSTRUCTION

Conductors: Solid annealed bare copper, as per BS 6360/IEC 60228 Class 1.

Insulation: Solid polyethylene as per IEC 60708/BS EN 50290-2-23/BS 6234/ASTM D 1248/NFC 32-060/VDE 0207.

Twisted Pairs: Insulated conductors are twisted into pairs with varying lay length to minimize crosstalk.

Cabling Element: Pairs or Quads.

Cable Core Assembly: Cables with 100 pairs or less are composed of 10-pair sub-units; cables with over 100 pairs are composed of 50 or 100-pair units. Any extra pairs form a separate unit. Units are identified by colour coded binders. Standard construction is per IEC 60708 in Cable Make Up Diagram.

Core Wrapping: One or more non-hygroscopic polyester tapes are helically or longitudinally laid with an overlap. These tapes furnish thermal, mechanical as well as high dielectric protection between shielding and individual conductors.

Moisture Barrier: A layer of aluminium tape (0.15mm) coated with PE-copolymer on one or both sides is applied longitudinally with overlap over the cable core to provide electrical shielding coverage and ensure a barrier against water vapor. In cables with more than 200 pairs, the aluminum tape may be corrugated for improved cable flexibility.

Sheath: Black low density polyethylene as per BS 6234/IEC 60708/ASTM D 1248, being able to withstand exposure to sunlight, temperature variations, ground chemicals and other environmental contaminants.

Ripcord: Ripcord may be provided for slitting the sheath longitudinally to facilitate its removal.

Spare Pairs (optional): Spare pairs may be incorporated in large pair cables.



Caledonian

Telephone Cables

www.caledonian-cables.com

marketing@caledonian-cables.com

Continuity Wire (optional): Tinned copper drain wire may be longitudinally laid to ensure electrical continuity of the screen.

COLOUR CODE

Standard colour code is per IEC 60708 given in Colour Code Chart

PHYSICAL AND THERMAL PROPERTIES

Temperature range during operation (fixed state): -30°C – +70°C

Temperature range during installation (mobile state): -20°C – +50°C

Minimum bending radius: 10 x Overall Diameter (unarmoured cables); 15 x Overall Diameter (armoured cables)

DIMENSION AND PARAMETERS

Caledonian Cable Code	No. of Pairs	Conductor Size	AWG Size	Conductor Diameter	Nominal Insulation Thickness	Nominal Diameter over Insulation	Nominal Sheath Thickness	Nom. Overall Diameter	Approx. Weight
		mm ²		mm	mm	mm	mm	mm	kg/km
TP708 -2Y(L)2Y -300P04	300	0.126	26	0.4	0.175	0.75	1.8	28	1034