



Caledonian



Tunnel Cables

www.caledonian-cables.com

marketing@caledonian-cables.com

Tunnel Cable

(N)SSHöU 3×16+3×16/3E



APPLICATIONS

For use in mines, quarries, industrial areas, construction sites agricultural operations and as trailing cable. The cables are also suitable for fixed application as power supply cable for underground mining and open-cast mining applications, for tunneling applications and similar applications.

STANDARDS

Construction: DIN VDE 0250-812

General Requirements: DIN VDE 0250-1

Guide Use: DIN VDE 0298-3

Electrical Tests: DIN VDE 0472-501, 503, 508

Non-Electrical Tests: DIN VDE 0472-401, 402, 602, 303, 615

Flame Retardant: VDE 0482-332-1-2, DIN EN 60332-1-2, IEC 60332-1

Under Fire Condition Tests: DIN VDE 0472-803, 804

Oil Resistant: HD/EN/IEC 60811-2-1, DIN VDE 0473-811-2-1

CABLE CONSTRUCTION

Conductors: Electrolytic, stranded, tinned copper wire DIN VDE 0295 Class 5.

Insulation: All cores are insulated with 3GI3 compound (acc.to DIN VDE 0207 Part 20).

Earth Conductor: Distributed as spiral of tinned copper wires over core insulating coverings (coding .../3E).

Lay Up: All cores are laid up in contact with each other and intersitial ground cores.

Inner Sheath: Special elastomeric compound GM1b (acc. to DIN VDE 02(17 Part 21).

Outer Sheath: Heavy-duty elastomer outer sheath 5GM5 (acc.to DIN VDE 0207 Part 21).

PHYSICAL AND THERMAL PROPERTIES

Rated Voltage: 0.6/1 KV

Max. Permissible Operating Voltage AC: 0.7/1.2 KV

Max. Permissible Operating Voltage DC: 0.9/1.8 KV

AC Test Voltage: 3 KV

Min Bending Radius Current Carrying: Acc. to VDE 0298-3

Current Carrying Capacities: DIN VDE 0298-4

Working Temperature:



Caledonian

Tunnel Cables

www.caledonian-cables.com

marketing@caledonian-cables.com

Fixed: -40°C - +80°C

Mobile: -25°C - +80°C

Max. Tensile Load of Cable: 15N/mm²

DIMENSION AND PARAMETERS

No. of Cores × Cross-sectional Area	Overall Diameter (min.)	Overall Diameter (max.)	Approx. Weight
No. × mm ²	mm	mm	kg/km
3×16+3×16/3E	27	30	1200