





Caledonian

Automotive Cables

www.caledonian-cables.com

marketing@caledonian-cables.com

AESSXF-ALS 2C1.25



APPLICATIONS

This XLPE insulated cable is used in low voltage signal circuits in automobiles. Superior heat resistant with irradiated PE. Suitable for the consideration of the flexibility and shielding characteristic. Shielding wire is consist of drain wire included Al-Mylar tape around core.

STANDARDS

JASO D608; HMC ES SPEC

CABLE CONSTRUCTION

Conductor: Annealed stranded copper

Insulation: XLPE

Shield: Al-Mylar Tape

Sheath: PVC

Standard Compliance: JASO D608; HMC ES SPEC

PHYSICAL AND THERMAL PROPERTIES

Operating temperature: -40 °C to +120 °C

DIMENSION AND PARAMETERS

| No. of Cores × Cross- sectional Area | No. and Dia. of Wires | Diameter of Conductor (max.) | Nominal Insulation Thickness | Overall Diameter (min.) | Overall Diameter (max.) | Approx. Weight | Electrical Resistance at 20°C (max.) |
|---|--------------------------|------------------------------------|------------------------------------|-------------------------------|-------------------------------|-------------------|---|
| No.×mm ² | no./mm | mm | mm | mm | mm | kg/km | MΩ/m |
| 2/1.25 | 37/0.21 | 1.5 | 0.3 | 5.5 | 5.7 | 48 | 15.2 |