





# Caledonian

Industrial Cables (Portuguese Standard)

[www.caledonian-cables.com](http://www.caledonian-cables.com)

[marketing@caledonian-cables.com](mailto:marketing@caledonian-cables.com)

## H07V-K



## APPLICATIONS

These are not suitable to be installed for laying in tubes, under and surface mounting of plaster and also in closed installation conduits. These are not allowed to install for direct laying on cable trays, channel or tanks. These types are permitted for the inner wiring of equipment, distributor and switchboards and also for protective laying to the lightings with a nominal voltage up to 1000 V alternating current or up to 750 V direct current against earth.

## STANDARDS

NP 2356/3

## VOLTAGE RATING

450/750V

## CABLE CONSTRUCTION

- Fine bare copper strands
- Strands to VDE-0295 Class-5, NP 2363 Class-5
- Special PVC T11 core insulation

## COLOUR CODE

Insulation Colour Code

Color coded to HD 308

Single core - Black, Blue, Green/Yellow, Red, Yellow, White, Violet, Brown, Grey, Orange, Pink

## PHYSICAL AND THERMAL PROPERTIES

- Test voltage: 2500 volts
- Flexing bending radius:  $12.5 \times \varnothing$
- Static bending radius:  $12.5 \times \varnothing$
- Flexing temperature:  $-5^{\circ} \text{C}$  to  $+70^{\circ} \text{C}$
- Static temperature:  $-30^{\circ} \text{C}$  to  $+80^{\circ} \text{C}$
- Short circuit temperature:  $+160^{\circ} \text{C}$
- Flame retardant: IEC 60332.1
- Insulation resistance:  $100 \text{ M}\Omega \times \text{km}$

## DIMENSION AND PARAMETERS



# Caledonian

Industrial Cables (Portuguese Standard)

[www.caledonian-cables.com](http://www.caledonian-cables.com)

[marketing@caledonian-cables.com](mailto:marketing@caledonian-cables.com)

No. of Cores × Cross- sectional Area	AWG Size	Nominal Insulation Thickness	Approx. Overall Diameter	Nominal Copper Weight	Approx. Weight
No.×mm <sup>2</sup>		mm	mm	kg/km	kg/km
1 x 240	500 MCM	2.2	27.1	2304	2270