





Caledonian

Industrial Cables (Portuguese Standard)

www.caledonian-cables.com

marketing@caledonian-cables.com

XV



APPLICATIONS

These cables are used for electricity supply in low voltage installation system, They are suitable for installation in indoors and outdoors, in cable ducts, underground, in power and switching stations, local energy distributions, industrial plants, where there is no risk of mechanical damage.

STANDARDS

IEC 60502-1

NP 2363

VOLTAGE RATING

600/1000 V

CABLE CONSTRUCTION

- Annealed copper conductor, class2 to NP 2363
- XLPE insulation
- Not fibrous and not hygroscopic filler(optional)
- Flexible PVC, type ST2 outer jacket

COLOUR CODE

Insulation Colour Code

Colour coded to HD 308

2 cores - Brown + Blue

PHYSICAL AND THERMAL PROPERTIES

- Test voltage: 3500 volts
- Minimum bending radius: 12 x Ø
- Operation temperature range: -15 °C to 90 °C
- Short-circuit temperature: 250 °C
- Flame retardant: IEC 60332.1
- Insulation resistance: 1000 MΩ x km

DIMENSION AND PARAMETERS

No. of Cores × Cross-sectional Area	Approx. Overall Diameter	Approx. Weight
-------------------------------------	--------------------------	----------------



Caledonian

Industrial Cables (Portuguese Standard)

www.caledonian-cables.com

marketing@caledonian-cables.com

No.×mm ²	mm	kg/km
2x10	14.5	365