





Caledonian

Industrial Cables (German Standard)

www.caledonian-cables.com

marketing@caledonian-cables.com

NAYY-O



APPLICATIONS

NAYY is used in power plants industrial and switching installations, in secondary distribution networks and other. These cables are preferentially used in outdoor applications, for indoor installations, in the open air, underground and in water where mechanical damage is not anticipated

STANDARDS

VDE 0276 part 603

IEC 60502

VOLTAGE RATING

600/1000V

CABLE CONSTRUCTION

- Stranded aluminium conductor
- VDE 0295 cl. 2 (round), BS 6360/IEC 60228 cl. 2
- PVC insulation type DIV4 acc. VDE0207
- PVC compound inner sheath
- PVC outer sheath type DMV5 acc. VDE 0207

COLOUR CODE

Insulation Colour Code

Color coded to DIN VDE 0293

Single core - Black, Blue, Green/Yellow, Red, Yellow, White, Violet, Brown, Grey, Orange, Pink

PHYSICAL AND THERMAL PROPERTIES

- Test voltage: 4000 volts
- Minimum bending radius: $12 \times \varnothing$
- Flexing temperature: -5°C to $+50^{\circ}\text{C}$
- Fixed installation temperature: -30°C to $+70^{\circ}\text{C}$
- Short circuit temperature: $+160^{\circ}\text{C}$
- Flame-retardant to DIN VDE 0472 part 804 class B/IEC 60332-1

DIMENSION AND PARAMETERS



Caledonian

Industrial Cables (German Standard)

www.caledonian-cables.com

marketing@caledonian-cables.com

No. of Cores × Cross-sectional Area	AWG Size	Approx. Overall Diameter	Aluminium Weight	Approx. Weight
No. × mm ²		mm	kg/km	kg/km
1x400	--	34	1109	1657