

Caledonian


Thermocouple Cables

www.caledonian-cables.com marketing@caledonian-cables.com

Multipair Individual/overall Screen with Armor and Lead Sheath

KX IS/OS & armored with lead sheath 24P1.3





APPLICATIONS

These cable can be used in cable tray or conduit to connect different types of thermocouple in industrial process controls, refineries, oil and gas plant. Excellent protection against corrosion, humidity and poor vibration resistance.

CABLE CONSTRUCTION

Conductor: Solid

Type applicable: KX, EX, JX, TX, NX, KCA, KCB, RCA, RCB, SCA, RCB, BC

Insulation: PVC, PE, XLPE or LSZH thermoplastic material

Individual screen: 24 µm aluminium / PETP tape over solid tinned copper drain wire, 0.6 mm

Wrapping: At least 1 layer of plastic tape

Overall screen: 24 µm aluminium / PETP tape over 7-stranded tinned copper drain wire, 0.5 mm²

Bedding: PE, PVC or LSZH thermoplastic material

Lead sheath: Lead alloy

Inner sheath: PVC or LSZH thermoplastic material

Armor: Galvanized round steel wires

Outer sheath: PVC or LSZH thermoplastic material

COLOUR CODE

According to IEC 60584-3

PHYSICAL AND THERMAL PROPERTIES

Flame retardancy: IEC 60332-1

Flame propagation: IEC 60332 cat. C

Temperature range: -30°C up to 70°C during operation. -5°C up to 50°C during installation.

DIMENSION AND PARAMETERS

No. of	Conductor	Nominal	Nominal	Lead	Nominal	Nominal	Nominal	Nom.	Approx.
Pairs	Size	Insulation	Bedding	Sheath	Inner	Armour	Outer	Overall	Weight
		Thickness	Thickness	Thickness	Sheath	Wire	Sheath	Diameter	
					Thickness	Diameter	Thickness		



Caledonian

Thermocouple Cables www.caledonian-cables.com

marketing@caledonian-cables.com

l		mm²	mm	kg/km						
	24	1.3	0.4	1.5	1.5	1.2	1.6	1.9	39.5	4653