



# Caledonian


IEC60092 Offshore & Marine Cables

www.caledonian-cables.com

marketing@caledonian-cables.com

## TFOI/ TFOU (MRE-2XCH) 150/250V XLPE Insulated, LSOH (SHF1) Sheathed, Armoured Flame Retardant Instrumentation & Control Cables 14P0.75

MRE-2XCH-14P0.75



### APPLICATIONS

These armoured cables are used on board of ships in all locations for fixed installations complying with IEC standards 60092-352. These cables are flame retardant, low smoke & halogen free, suitable for installations on passenger ships, as on other commercial vessels.

### STANDARDS

IEC 60092-350/360/376/IEC 60332-1

IEC 60332-3-22/IEC 60754-1/2/IEC 61034

### CABLE CONSTRUCTION

Conductors: Class 2 stranded copper conductor.

Insulation: XLPE.

Cabling Element: Pair.

Inner Covering: Lapped polyester tape.

Armour: Copper wire braid.

Outer Sheath: LSOH (SHF1). SHF2 can be offered upon request.

### COLOUR CODE

Pair: White/blue with printed pair number and core number.

### PHYSICAL AND THERMAL PROPERTIES

Bending Radius for Fixed Installations: 6×OD

Temperature Range: -30°C ~ +80°C

### DIMENSION AND PARAMETERS

No. of Cores × Cross-sectional Area	Nominal Insulation Thickness	Nominal Sheath Thickness	Nom. Overall Diameter	Approx. Weight
No. × mm <sup>2</sup>	mm	mm	mm	kg/km
14×2×0.75	0.5	2	20.6	610