





Caledonian

Industrial Cables (UL Standard)

www.caledonian-cables.com

marketing@caledonian-cables.com

EPR/Copper Tape Shield with Overall PVC Jacket Medium-Voltage Power, Shielded, 15KV, UL Type MV-105 133% Ins.Level, 220 Mils, Three Conductor 3C4/0AWG



APPLICATIONS

These cables are suited for use in a broad range of commercial, industrial and utility applications, where reliability is the major concern, space is limited and ease of installation is critical. Besides, they are installed in wet or dry locations accordance with NEC. Also in aerial, direct burial, conduit, open tray and underground duct installations.

STANDARDS

National Electric Code (NEC)

ICEA S-93-639/NEMA WC74

UL 1072

ICEA S-97-682

AEIC CS8

Meets EPA 40 CFR, Part 261 for leachable lead content per TCLP method

UL 1685 (70,000 BTU/hr)

Optional Flame Tests:

IEEE 1202 (70,000 BTU/hr)/CSA FT4

ICEA T-29-520 (210,000 BTU/hr)

VOLTAGE RATING

15KV

CABLE CONSTRUCTION

Conductor: Annealed bare copper Class B strand.

Extruded Strand Shield (ESS): Extruded thermoset semi-conducting stress-control layer over conductor.

Insulation: Ethylene Propylene Rubber (EPR) insulation, colored to contrast with the black conducting shield layers.

Extruded Insulation Shield (EIS): Thermoset semi-conducting polymeric layer free stripping from insulation.

Metallic Shield: 5mil annealed copper tape with an overlap of 25%.

Grounding Conductor: 1 bare grounding conductor may be in contact with metallic shielding tape.

Overall Jacket: Flame-retardant Polyvinyl Chloride (PVC), UV resistance, hydrocarbon resistance, oil resistance, anti rodent and anti termite properties can be offered as option.

DIMENSION AND PARAMETERS



Caledonian

Industrial Cables (UL Standard)

www.caledonian-cables.com

marketing@caledonian-cables.com

AWG Size	Conductor Diameter	Conductor Diameter	Nominal Diameter over Insulation (min.)	Nominal Diameter over Insulation (min.)	Nominal Diameter over Insulation (max.)	Nominal Diameter over Insulation (max.)	Ground Wire AWG	Nominal Jacket Thickness in	Nominal Jacket Thickness mm	Approximate Overall Diameter in	Approximate Overall Diameter mm	Approximate Weight kg/ km	Approximate Weight LBS/ MFT	Impact In Air	Impact GND.	Impact Tray
4/0	0.48	12.19	0.92	23.37	1.005	25.53	3	0.11	2.79	2.52	64.01	6255	4203	320	305	360