


## Caledonian

Industrial Cables (UL Standard) www.caledonian-cables.com marketing@caledonian-cables.com

#### EPR/HYP, Medium-Voltage Power, Non-Shielded 2400V, UL Type MV-90 1C1000AWG





#### **APPLICATIONS**

These cables are used in these applications: pulp and paper mills, petrochemical plants, sewage treatment facilities, water treatment plants, steel mills, textile mills, utility power generating stations, scrubbers and other environmental protections systems, railroad and mining facilities. Also, they are used in industrial and utility applications, where ease of installation is a major concern because of limited space and exposure to personnel is minimal, in wet or dry locations when installed in accordance with NEC, and use in aerial, conduit, open tray and underground duct installations.

#### STANDARDS

National Electric Code (NEC) ICEA S-96-659/NEMA WC71 UL 1072 FAA L824 specification for cable for Underground Airport Lighting Circuits Listed "oil-resistant II" Meets EPA 40 CFR, Part 261 for leachable lead content per TCLP method

#### **VOLTAGE RATING**

2400V

#### CABLE CONSTRUCTION

Conductor: Annealed bare copper Class B strand.

Extruded Strand Shield (ESS): Extruded thermoset semi-conducting stress-control layer over conductor. Insulation: Ethylene Propylene Rubber (EPR) insulation, colored to contrast with the black jacket material. Jacket: Low-Lead Chlorosulfonated Polyethylene (CSPE)/ Elastomer blend.

#### DIMENSION AND PARAMETERS

AW	GO	Conduct	Conducto	Nominal	Nominal	Nominal	Nominal	Nominal	Nominal	Approx.	Approx.	Approx.	Approx.
Size	e	Diameter	Diameter	Extruded	Extruded	nsulatior	nsulatior	Diameter	Diametei	Overall	Overall	Weight	Weight
				Strand	Strand	Thicknes	Thicknes	over	over	Diameter	Diameter		
				Shield	Shield			nsulation	nsulatior				
				Diametei	Diameter								
		in	mm	in	mm	in	mm	in	mm	in	mm	kg/km	LBS/
													MFT



# Caledonian

### Industrial Cables (UL Standard)

www.caledonian-cables.com marketing@caledonian-cables.com

10	000	1.06	26.92	1.09	27.69	0.155	3.94	1.42	36.07	1.7	43.18	5823	3913	
----	-----	------	-------	------	-------	-------	------	------	-------	-----	-------	------	------	--