

# Caledonian


### Industrial Cables (UL Standard)

www.caledonian-cables.com

marketing@caledonian-cables.com

## EPR/HYP, Medium-Voltage Power, Non-Shielded 2400V, UL Type MV-90 1C250AWG





#### **APPLICATIONS**

These cables are used in these applications: pulp and paper mills, petrochemical plants, sewage treatment facilities, water treatment plants, steel mills, textile mills, utility power generating stations, scrubbers and other environmental protections systems, railroad and mining facilities. Also, they are used in industrial and utility applications, where ease of installation is a major concern because of limited space and exposure to personnel is minimal, in wet or dry locations when installed in accordance with NEC, and use in aerial, conduit, open tray and underground duct installations.

#### **STANDARDS**

National Electric Code (NEC) ICEA S-96-659/NEMA WC71

UL 1072

FAA L824 specification for cable for Underground Airport Lighting Circuits

Listed "oil-resistant II"

Meets EPA 40 CFR, Part 261 for leachable lead content per TCLP method

#### **VOLTAGE RATING**

2400V

#### CABLE CONSTRUCTION

Conductor: Annealed bare copper Class B strand.

Extruded Strand Shield (ESS): Extruded thermoset semi-conducting stress-control layer over conductor. Insulation: Ethylene Propylene Rubber (EPR) insulation, colored to contrast with the black jacket material.

Jacket: Low-Lead Chlorosulfonated Polyethylene (CSPE)/ Elastomer blend.

#### **DIMENSION AND PARAMETERS**

	Conducto Diameter											
OIZE	Diameter	Diametei	Strand	Strand	Thicknes	hicknes	over	over	Diameter			vveignt
			Shield Diameter	Shield Diameter			nsulation	nsulatior				
	in	mm	in	mm	in	mm	in	mm	in	mm	kg/km	LBS/ MFT



# Caledonian

Industrial Cables (UL Standard)

www.caledonian-cables.com marketing@caledonian-cables.com

	250	0.53	13.46	0.55	13.97	0.14	3.56	0.84	21.34	1.08	27.43	1761	1183
-1		1											