


Caledonian

Industrial Cables (UL Standard)

www.caledonian-cables.com marketing@caledonian-cables.com

EPR/HYP, Medium-Voltage Power, Non-Shielded 2400V, UL Type MV-90 1C4AWG





APPLICATIONS

These cables are used in these applications: pulp and paper mills, petrochemical plants, sewage treatment facilities, water treatment plants, steel mills, textile mills, utility power generating stations, scrubbers and other environmental protections systems, railroad and mining facilities. Also, they are used in industrial and utility applications, where ease of installation is a major concern because of limited space and exposure to personnel is minimal, in wet or dry locations when installed in accordance with NEC, and use in aerial, conduit, open tray and underground duct installations.

STANDARDS

National Electric Code (NEC) ICEA S-96-659/NEMA WC71

UL 1072

FAA L824 specification for cable for Underground Airport Lighting Circuits

Listed "oil-resistant II"

Meets EPA 40 CFR, Part 261 for leachable lead content per TCLP method

VOLTAGE RATING

2400V

CABLE CONSTRUCTION

Conductor: Annealed bare copper Class B strand.

Extruded Strand Shield (ESS): Extruded thermoset semi-conducting stress-control layer over conductor. Insulation: Ethylene Propylene Rubber (EPR) insulation, colored to contrast with the black jacket material.

Jacket: Low-Lead Chlorosulfonated Polyethylene (CSPE)/ Elastomer blend.

DIMENSION AND PARAMETERS

	AWG	Conduct6	Conducto	Nominal	Nominal	Nominal	Nominal	Nominal	Nominal	Approx.	Approx.	Approx.	Approx.
1	Size	Diameter	Diamete	Extruded	Extruded	nsulation	nsulatior	Diameter	Diameter	Overall	Overall	Weight	Weight
1				Strand	Strand	Thicknes	Thickness	over	over	Diameter	Diameter		
1				Shield	Shield			nsulation	nsulatior				
ı				Diameter	Diameter								
ĺ		in	mm	in	mm	in	mm	in	mm	in	mm	kg/km	LBS/
1													MFT



Caledonian

Industrial Cables (UL Standard)

www.caledonian-cables.com marketing@caledonian-cables.com

4 0.22 5.59 0.23 5.84 (125 3.18 0.49	12.45 0.66 16.7	6 458 308
-------------------------	---------------	-----------------	-----------