





# Caledonian

Industrial Cables to British Standard

[www.caledonian-cables.com](http://www.caledonian-cables.com)

[marketing@caledonian-cables.com](mailto:marketing@caledonian-cables.com)

6181Y to BS 6004



## APPLICATIONS

These cables are designed for surface wiring where there is little risk of mechanical damage and are suitable for use in electrical installations such as power and lighting.

## VOLTAGE RATING

300/500V

## CABLE CONSTRUCTION

- Bare copper conductor
- Solid to BS 6360 CL-1 or IEC 60228 CL-1
- PVC insulation Type T11 to BS7655
- PVC sheath Type 6 to BS7655

## COLOUR CODE

Black, Blue, Brown

## PHYSICAL AND THERMAL PROPERTIES

- Minimum bending radius: 3xoverall diameter
- Operating temperature: -15° C to +70° C
- Insulation resistance: 10 MΩxkm
- Flame retardant: IEC 60332.1

## DIMENSION AND PARAMETERS

No. of Cores × Cross-sectional Area	AWG Size	Nominal Insulation Thickness	Nominal Sheath Thickness	Approx. Overall Diameter	Approx. Weight
No.×mm <sup>2</sup>		mm	mm	mm	kg/km
1x2.5	16(solid)	0.8	0.8	5.8	52