




Caledonian

Military Cables

www.caledonian-cables.com

marketing@caledonian-cables.com

MIL-W-25038/1 1C10AWG



APPLICATIONS

These Composite Inorganic Dielectric insulated single-core MIL-W-25038/1 cables are used for critical circuit applications where wires must operate in extremely harsh environments, under vibration, and with direct flame exposure. This heavy-duty, non-asbestos construction offers excellent mechanical performance and abrasion resistance.

VOLTAGE RATING

600V

CABLE CONSTRUCTION

Conductor: Stranded 27% nickel coated copper conductor

Insulation: Composite inorganic dielectric insulation

Jacket: Polytetrafluoroethylene (PTFE) coated fiberglass braid jacket

Identification: Surface printed per MIL-W-25038

COLOUR CODE

Color coded: MIL-STD-104

PHYSICAL AND THERMAL PROPERTIES

Temperature Range: -55°C to +260°C

DIMENSION AND PARAMETERS

AWG Size	Conductor Stranding	Conductor Diameter	Conductor Diameter	Overall Diameter (min.)	Overall Diameter (min.)	Overall Diameter (max.)	Overall Diameter (max.)	Approx. Weight	Max. Resistance at 20°C
		in	mm	in	mm	in	mm	LBS/MFT	OHMS/MFT
10	49/27	0.122	3.099	0.21	5.334	0.23	5.842	55	1.68