




# Caledonian

Military Cables

www.caledonian-cables.com

marketing@caledonian-cables.com

## MIL-W-25038/1 1C8AWG



### APPLICATIONS

These Composite Inorganic Dielectric insulated single-core MIL-W-25038/1 cables are used for critical circuit applications where wires must operate in extremely harsh environments, under vibration, and with direct flame exposure. This heavy-duty, non-asbestos construction offers excellent mechanical performance and abrasion resistance.

### VOLTAGE RATING

600V

### CABLE CONSTRUCTION

Conductor: Stranded 27% nickel coated copper conductor

Insulation: Composite inorganic dielectric insulation

Jacket: Polytetrafluoroethylene (PTFE) coated fiberglass braid jacket

Identification: Surface printed per MIL-W-25038

### COLOUR CODE

Color coded: MIL-STD-104

### PHYSICAL AND THERMAL PROPERTIES

Temperature Range: -55°C to +260°C

### DIMENSION AND PARAMETERS

| AWG Size | Conductor Stranding | Conductor Diameter | Conductor Diameter | Overall Diameter (min.) | Overall Diameter (min.) | Overall Diameter (max.) | Overall Diameter (max.) | Approx. Weight | Max. Resistance at 20°C |
|----------|---------------------|--------------------|--------------------|-------------------------|-------------------------|-------------------------|-------------------------|----------------|-------------------------|
|          |                     | in                 | mm                 | in                      | mm                      | in                      | mm                      | LBS/MFT        | OHMS/MFT                |
| 8        | 133/29              | 0.19               | 4.039              | 0.256                   | 6.502                   | 0.28                    | 7.112                   | 85             | 0.936                   |