




Caledonian

Military Cables

www.caledonian-cables.com

marketing@caledonian-cables.com

MIL-W-25038/3 Thermazone IIIK 1C18AWG



APPLICATIONS

These PTFE insulated single-core MIL-W-25038/3 cables are used in such aerospace applications as engine compartments, fire detection circuits, flight-critical circuits, and fly-by-wire systems. MIL-W-25038/3(Thermazone IIIK) wires are designed for critical circuit applications where wires must operate in extremely harsh environments, under vibration, and with direct flame exposure.

VOLTAGE RATING

600V

CABLE CONSTRUCTION

Conductor: Stranded 27% Nickel coated copper conductor

Insulation:

Outer: PTFE/polyimide tape fluid barrier

Inner: Inorganic dielectric

Jacket: Fused high-performance polytetrafluoroethylene (PTFE) tape jacket

Identification: Surface printed per MIL-W-25038

COLOUR CODE

Color coded: MIL-STD-104

PHYSICAL AND THERMAL PROPERTIES

Temperature Range: -55°C to +260°C

DIMENSION AND PARAMETERS

AWG Size	Conductor Stranding	Conductor Diameter	Conductor Diameter	Overall Diameter (min.)	Overall Diameter (min.)	Overall Diameter (max.)	Overall Diameter (max.)	Approx. Weight	Max. Resistance at 20°C
		in	mm	in	mm	in	mm	LBS/MFT	OHMS/MFT
18	19/30	0.05	1.27	0.065	1.651	0.097	2.464	10.5	8.5