





# Caledonian

Military Cables

[www.caledonian-cables.com](http://www.caledonian-cables.com)

[marketing@caledonian-cables.com](mailto:marketing@caledonian-cables.com)

## MIL-W-81822/6 Type A 1C22AWG



## APPLICATIONS

These extruded thin wall PTFE (polyvinylidene fluoride) insulated single-core MIL-W-81822/6 cables are used in back panel wire wrap applications. These wires have solid conductors for wire-wrap applications such as back panel wiring, with a choice of three conductor materials.

## VOLTAGE RATING

300V

## CABLE CONSTRUCTION

Conductor: Silver-plated ETP copper

Insulation: Thin-wall extruded PTFE

## COLOUR CODE

MIL-STD-104(See page 65)

## PHYSICAL AND THERMAL PROPERTIES

Temperature Range: 200°C

## DIMENSION AND PARAMETERS

AWG Size	Conductor Stranding	Conductor Diameter	Conductor Diameter	Overall Diameter (min.)	Overall Diameter (min.)	Overall Diameter (max.)	Overall Diameter (max.)	Approx. Weight	Max. Resistance at 20°C
		in	mm	in	mm	in	mm	LBS/MFT	OHMS/MFT
22	Solid	0.0253	0.643	0.046	1.17	0.05	1.27	3.4	16.8