



# Caledonian


Mining Cables (VDE Standard)

www.caledonian-cables.com

marketing@caledonian-cables.com

## Cables for Underground Mining

NSSHCGEOEU 0.6/1kV Coal Cutter Cable (Low Tensile Stress) 3×95/50KON+2ST+UEL



## APPLICATIONS

These cables are used for the connection of mobile machines under extremely high mechanical loads, predominantly in mining situations, e.g. for coal-cutting machines, suitable for extreme bending loads under low tensile stress.

## STANDARDS

VDE 0250 Part 812

## CABLE CONSTRUCTION

Conductors: Flexible stranded tinned copper conductor.

Insulation: Heat resistant 3GI3 rubber based on EPR.

Outer Conductor Layer: Easy strippable outer conductive layer.

Pilot Cores: Copper strand and steel braid conductor capable of expansion and compression with EPR rubber insulation.

Monitoring Cores: Spiral of tinned copper wires above the pilot cores, covered with a semiconductive tape.

Inner Sheath: Rubber type GM1b.

Armour/Earth Conductor: Concentric earth conductor as spiral of copper and steel wires, fibreglas tape, embedded in the outer sheath which prevents sheath exchanging.

Outer Sheath: Rubber type 5GM5, abrasion and tear resistant, oil resistant and flame retardant.

## DIMENSION AND PARAMETERS

No. of Cores × Cross-sectional Area	Overall Diameter (min.)	Overall Diameter (max.)	Approx. Weight
No. × mm <sup>2</sup>	mm	mm	kg/km
3×95/50KON+2ST+UEL	58	62	7180