


# Caledonian

Mining Cables (ICEA & CSA Standard) www.caledonian-cables.com marketing@caledonian-cables.com

### Portable Power Cables

Type G Two-Conductor Round Portable Power Cable 2kV 2C6AWG





## **APPLICATIONS**

These cables are designed for use in heavy duty services as power supply cable, mobile and portable electrical.

#### **STANDARDS**

ICEA S-75-381/NEMA WC 58 ASTM B 172/ASTM B 33 CAN/CSA C22.2 No. 96

#### CABLE CONSTRUCTION

Conductors:Stranded annealed tinned copper conductor. Insulation:Ethylene Propylene Rubber (EPR). Grounding Conductor:Tinned copper conductor with an optional green outer covering. Jacket:Reinforced heavy-duty/extra-heavy-duty Chlorinated Polyethylene (CPE), black. (Cables having a nominal outside diameter of more than 2.0 inches require extra-heavy-duty jackets.)

Options:

Other jacket materials such as CSP/PCP/NBR/PVC are available upon request. Two-layer jacket with reinforcing fibre between the two layers can be offered as an option.

#### COLOUR CODE

Conductor Identification According to ICEA S-75-381: 2 Cores:Black+White

#### PHYSICAL AND THERMAL PROPERTIES

Minimum Bending Radius: 6×OD Maximum Conductor Operating Temperature: +90°C

#### DIMENSION AND PARAMETERS

No. of										Ampacity
Cores	Size	Strands	Insulation	Insulation					<u> </u>	
			Thickness	Thickness	Thickness	Thickness	Diameter	Diameter		



# Caledonian

Mining Cables (ICEA & CSA Standard)

www.caledonian-cables.com

marketing@caledonian-cables.com

			in	mm	AWG	in	mm	in	mm	kg/km	amps
2	6	259	0.06	1.5	10	0.125	3.2	0.93	23.6	967	95