

Caledonian

Mining Cables (ICEA & CSA Standard)

www.caledonian-cables.com marketing@caledonian-cables.com

Mine Power Feeder Cables

Type MP-GC Three-Conductor Mine Power Feeder Cable, CPE Jacket 15kV 3C250AWG





APPLICATIONS

These cables are designed for connections between units of mine distribution systems, suitable for installed in duct, conduit or open air and for direct burial in wet and dry locations.

STANDARDS

ICEA S-75-381/NEMA WC 58 ASTM B-8 CAN/CSA-C22.2 No.96

CABLE CONSTRUCTION

Conductors:Stranded annealed bare copper conductor.

Conductor Shield:Conducting layer.

Insulation: Ethylene Propylene Rubber (EPR).

Insulation Shield:Conducting layer + copper tape.

Ground Check Conductor:Copper conductor with a yellow polypropylene insulation.

Grounding Conductor: Tinned copper conductor. Jacket: Chlorinated Polyethylene (CPE), black.

Options:

Other jacket materials such as CSP/PCP/NBR/PVC/TPU are available upon request.

COLOUR CODE

Conductor Identification According to ICEA S-75-381:

3 Cores:Black+White+Red

PHYSICAL AND THERMAL PROPERTIES

Minimum Bending Radius: 12×OD

Maximum Conductor Operating Temperature: +90°C

DIMENSION AND PARAMETERS



Caledonian

Mining Cables (ICEA & CSA Standard)

www.caledonian-cables.com marketing@caledonian-cables.com

No. of	AWG	No. of	Nominal	Nominal	Ground	Ground	Nominal	Nominal	Approx.	Approx.	Approx.	Ampacity
Cores	Size	Strands	Insulation	nsulatior	Wire	Check	Jacket	Jacket	Overall	Overall	Weight	
		-	Thicknes	Thicknes	(Conducto	Thicknes	Thickness	Diameter	Diameter		
			in	mm	AWG	AWG	in	mm	in	mm	kg/km	amps
3	250	37	0.175	4.4	1/0	8	0.14	3.6	2.48	63	8359	359