



Caledonian


Mining Cables (ICEA & CSA Standard)

www.caledonian-cables.com

marketing@caledonian-cables.com

Mine Power Feeder Cables

Type MP-GC Three-Conductor Mine Power Feeder Cable, CPE Jacket 5kV 3C350AWG



APPLICATIONS

These cables are designed for connections between units of mine distribution systems, suitable for installed in duct, conduit or open air and for direct burial in wet and dry locations.

STANDARDS

ICEA S-75-381/NEMA WC 58

ASTM B-8

CAN/CSA-C22.2 No.96

CABLE CONSTRUCTION

Conductors: Stranded annealed bare copper conductor.

Conductor Shield: Conducting layer.

Insulation: Ethylene Propylene Rubber (EPR).

Insulation Shield: Conducting layer + copper tape.

Ground Check Conductor: Copper conductor with a yellow polypropylene insulation.

Grounding Conductor: Tinned copper conductor.

Jacket: Chlorinated Polyethylene (CPE), black.

Options:

Other jacket materials such as CSP/PCP/NBR/PVC/TPU are available upon request.

COLOUR CODE

Conductor Identification According to ICEA S-75-381:

3 Cores: Black+White+Red

PHYSICAL AND THERMAL PROPERTIES

Minimum Bending Radius: 12×OD

Maximum Conductor Operating Temperature: +90°C

DIMENSION AND PARAMETERS



Caledonian

Mining Cables (ICEA & CSA Standard)

www.caledonian-cables.com

marketing@caledonian-cables.com

| No. of Cores | AWG Size | No. of Strands | Nominal Insulation Thickness in | Nominal Insulation Thickness mm | Ground Wire AWG | Ground Check Conductor AWG | Nominal Jacket Thickness in | Nominal Jacket Thickness mm | Approx. Overall Diameter in | Approx. Overall Diameter mm | Approx. Weight kg/km | Ampacity amps |
|--------------|----------|----------------|------------------------------------|------------------------------------|--------------------|----------------------------------|-----------------------------------|-----------------------------------|-----------------------------------|-----------------------------------|-------------------------|------------------|
| 3 | 350 | 37 | 0.09 | 2.3 | 2/0 | 8 | 0.14 | 3.6 | 2.31 | 58.7 | 9019 | 435 |